

Application No. 10/096,676  
Amendment dated October 26, 2004  
Reply to Office action of August 10, 2004

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**CLAIMS:**

Please amend claims 8 and 12, as follows:

1. (Previously Presented) A hand-held electronic device including a navigational component, comprising:

a housing, the housing having an opening therein;

a display viewable through a touch panel mounted in the opening of the housing,

the touch panel including:

a layer of rigid material; and

a flexible substrate layer positioned near the layer of rigid material;

a mounting member circumscribing the opening for use in providing a watertight seal, the mounting member including:

a first leg positioned away from a top of the housing and attached to a first shock absorbing member; and

a second leg positioned away from the top of the housing and attached to the first shock absorbing member and an adhesive.

Application No. 10/096,676  
Amendment dated October 26, 2004  
Reply to Office action of August 10, 2004

2. (Original) The hand-held electronic device including a navigational component of claim 1 wherein the adhesive is a flexible adhesive.
3. (Original) The hand-held electronic device including a navigational component of claim 1 wherein the adhesive is a flexible, waterproof adhesive.
4. (Original) The hand-held electronic device including a navigational component of claim 1, wherein the adhesive is curable using an ultraviolet light.
5. (Original) The hand-held electronic device including a navigational component of claim 1, wherein the adhesive is rigid.
6. (Previously Presented) The hand-held electronic device including a navigational component of claim 1, wherein the first shock absorbing member includes a viscoelastic material.
7. (Previously Presented) The hand-held electronic device including a navigational component of claim 6, wherein the first shock absorbing member includes a layer of foam material.

Application No. 10/096,676  
Amendment dated October 26, 2004  
Reply to Office action of August 10, 2004

8. (Currently Amended) The hand-held electronic device including a navigational component of claim 1, further comprising:

a backing member that fits within the housing, the backing member having a portion positioned near the touch panel; and

a second shock ~~absorber~~ absorbing member opposite the first shock absorbing member and including a portion which is sandwiched between the backing member and the layer of rigid material of the touch panel.

9. (Previously Presented) The hand-held electronic device including a navigational component of claim 1, further comprising:

a backing member that fits within the housing, the backing member having a portion positioned near the layer of rigid material of the touch panel;

a first shock absorbing member including a portion which is sandwiched between the flexible member of the touch panel and the mounting member; and

a second shock absorbing member including a portion which is sandwiched between the backing member and the layer of rigid material of the touch panel.

10. (Original) The hand-held electronic device including a navigational component of claim 1, wherein the mounting member is molded with the housing.

Application No. 10/096,576  
Amendment dated October 26, 2004  
Reply to Office action of August 10, 2004

11. (Original) The hand-held electronic device including a navigational component of claim 1, wherein the mounting member is integral with the housing.

12. (Currently Amended) A hand-held electronic device including a navigational component comprising:

- a housing, the housing having an opening therein;
- a display viewable through a touch panel positioned in the opening of the housing, the touch panel including:
  - a layer of rigid material; and
  - a flexible substrate layer positioned near the layer of rigid material;
- a mounting member circumscribing the opening, the mounting member including a pocket for holding an adhesive and applying the adhesive about the periphery of the touch panel;
- a processor located within the housing;
- a memory in communication with the processor, the touch panel in communication with the processor and the memory, the processor and memory capable of performing a route calculation viewable on the display; and
- a fluid seal securing the touch panel to the housing, the fluid seal being compressed ~~toward the housing by~~ disposed in front of the periphery of and around an outer edge of the touch panel and compressed toward the mounting member by a backing bracket to provide a water proof seal and a shock mount.

Application No. 10/096,676  
Amendment dated October 26, 2004  
Reply to Office action of August 10, 2004

13. (Original) The hand-held electronic device including a navigational component of claim 12, further comprising a device capable of performing a dead reckoning calculation.

14. (Previously Presented) The hand-held electronic device including a navigational component of claim 13, wherein the device capable of performing a dead reckoning calculation includes a rate gyro.

Application No. 10/096,676  
Amendment dated October 26, 2004  
Reply to Office action of August 10, 2004

**15. (Previously Presented) A hand-held electronic device comprising:**

- a housing, the housing having an opening therein;**
- a processor located within the housing;**
- a memory located within the housing, the memory in communication with the processor;**
- a display in communication with the processor and the memory, the display viewable through a touch panel mounted in the opening in the housing;**
- a first component adapted to perform a first function; and**
- a second component adapted to perform a second function, one of the first component and the second component including a navigational component, the navigational component including a dead reckoning component located within the housing, the dead reckoning component in communication with the processor and operable to detect a position of the hand-held electronic device when GPS signals are unavailable and an antenna adapted to acquire position signals, the housing including a flange around the opening in the housing, the flange further comprising:**
  - a fluid seal to prevent fluid flow past the touch panel and into the housing;**
  - and**
  - a shock mount.**

**16. (Original) The hand-held electronic device including a navigational component of claim 15, wherein the antenna is an internal patch antenna.**

Application No. 10/098,676  
Amendment dated October 26, 2004  
Reply to Office action of August 10, 2004

17. (Original) The hand-held electronic device of claim 15, wherein the touch panel further comprises:
- a layer of rigid material; and
  - a flexible substrate layer positioned near the layer of rigid material.
18. (Original) The hand-held electronic device of claim 15, further comprising an instruction set for controlling the processor and memory to perform a route calculation.
19. (Original) The hand-held electronic device of claim 15, further comprising an instruction set for controlling the processor and memory to perform a route calculation, the instruction set including user interface instructions to display the results of the route calculation on the display.
20. (Original) The hand-held electronic device of claim 15, wherein the mounting member includes a flexible adhesive.
21. (Previously Presented) The hand-held electronic device of claim 20, wherein the mounting member includes a groove for holding the flexible adhesive.
22. (Original) The hand-held electronic device of claim 15, wherein the fluid seal includes a gasket.

Application No. 10/096,676  
Amendment dated October 26, 2004  
Reply to Office action of August 10, 2004

23. (Original) The hand-held device of claim 15, wherein the shock mount includes a viscoelastic material.



Application No. 10/098,676  
Amendment dated October 26, 2004  
Reply to Office action of August 10, 2004

**24. (Previously Presented) A navigation system comprising:**

- a mass storage device adapted to store navigation data;**
- a server adapted to communicate with the mass storage device; and**
- a portable, multi-function electronic device further comprising:**
  - a housing having an opening therein;**
  - a processor located within the housing;**
  - a memory located within the housing, the memory in communication with the processor;**
  - a display in communication with the processor and the memory, the display viewable through a touch panel mounted to the opening in the housing, the housing including a flange around the opening in the housing, the flange further comprising:**
    - a fluid seal securing the touch panel to the housing, the fluid seal being compressed in a first direction by the touch panel and in a second direction by a backing bracket such that fluid flow past the touch panel and into the housing is prevented; and**
    - a shock mount; and**
  - an antenna within the housing for communicating with the server, the multi-function electronic device including a navigation device adapted to perform a route calculation.**

Application No. 10/096,676  
Amendment dated October 26, 2004  
Reply to Office action of August 10, 2004

25. (Original) The navigation system of claim 24, wherein the navigation device further comprises an instruction set for controlling the processor and memory to perform a route calculation.
26. (Original) The navigation system of claim 25, wherein the instruction set includes user interface instructions for displaying the results of the route calculation on the display.
27. (Original) The navigation system of claim 25, Wherein at least a portion of the instruction set is resides within the processor and memory.
28. The navigation system of claim 25, wherein at least a portion of the instruction set is transmitted to the portable, multi-function electronic device from the server.

Application No. 10/096,678  
Amendment dated October 26, 2004  
Reply to Office action of August 10, 2004

Please add claims 29 and 30, as follows:

29. (New) A hand-held electronic device including a navigational component, comprising:
- a housing, the housing having an opening therein;
  - a display viewable through a touch panel mounted in the opening of the housing, the touch panel including -
    - a layer of rigid material, and
    - a flexible substrate layer positioned near the layer of rigid material;
  - a mounting member circumscribing the opening for use in providing a watertight seal, the mounting member including -
    - a first leg positioned away from a top of the housing and attached to a first shock absorbing member, and
    - a second leg positioned away from the top of the housing and attached to the first shock absorbing member and an adhesive;
  - a backing member that fits within the housing, the backing member having a portion positioned near the layer of rigid material of the touch panel;
  - the first shock absorbing member including a portion which is sandwiched between the flexible member of the touch panel and the mounting member; and
  - a second shock absorbing member including a portion which is sandwiched between the backing member and the layer of rigid material of the touch panel.

Application No. 10/096,676  
Amendment dated October 26, 2004  
Reply to Office action of August 10, 2004

30. (New) A hand-held electronic device including a navigational component, comprising:
- a housing, the housing having an opening therein;
  - a display viewable through a touch panel mounted in the opening of the housing, the touch panel including -
    - a layer of rigid material, and
    - a flexible substrate layer positioned near the layer of rigid material;
  - a mounting member circumscribing the opening for use in providing a watertight seal, the mounting member including -
    - a leg positioned away from the top of the housing and attached to a first shock absorbing member and an adhesive, and
  - wherein the first shock absorbing member is pressed against the flexible layer of the touch panel;
  - a backing member that fits within the housing, the backing member having a portion positioned near the layer of rigid material of the touch panel;
  - a second shock absorbing member including a portion which is sandwiched between the backing member and the layer of rigid material of the touch panel; and
  - wherein the adhesive is disposed along a periphery of the flexible layer and around an outer edge of the layer of rigid material the touch panel to provide a water proof seal and a shock mount.

No new matter has been added as a result of these changes.